

## **DECLARATION OF PERFORMANCE**

## CE Marking - Declaration of Performance Ffestiniog County Grade Roofing Slate



Welsh Slate roofing products conform to the requirements of the CE mark. The following table provides the necessary information required to demonstrate conformity of Ffestiniog County Grade Roofing Slate

Welsh Slate, Penrhyn Quarry, Bethesda, Bangor, Gwynedd, LL57	4YG United Kingdom
Ref: BPWS 123	
EN 12326-1:2014 System of Attestation = AVCP System 4	
Ffestiniog County	
Intended to be used as discontinuous roofing and external claddi	ng
Dimensional variation	
Nominal thickness	7 mm
Individual thickness	7 mm (< +/- 35%)
Deviation of length and width	Complies
Deviation of edge straightness	Complies
Deviation of rectangularity	Complies
Mechanical resistance (Characteristic modulus of rupture)	
Transverse	55.2 N/mm²
Longitudinal	41.7 N/mm²
Water permeability - water absorption	<b>A1</b> (≤ 0.6%)
Apparent calcium carbonate content	≤ 5%
Durability	
Water absorption	<b>A1</b> (≤0.6%)
Freeze-thaw cycling	Required
Thermal cycling	Т1
Sulphur dioxide exposure	S1
Non-carbonate carbon content	Complies: ≤ 2%
Release of dangerous substances: None in conditions of use as roo	ofing or external cladding
External fire performance: Deemed to satisfy	
Signed on behalf of the Manufacturer:	Sean G Edwards - Operations Manager